

REMARKS

In response to the Notice of Non-Compliant Amendment dated February 12, 2002, applicant is enclosing herewith a marked-up version of the replacement paragraph 2 on page 5 of his application.

Any inconvenience to the Examiner is sincerely regretted.

Respectfully submitted,



Keith D. Nowak
Reg. No. 27,367
LIEBERMAN & NOWAK, LLP
350 Fifth Avenue
New York, NY 10118
(212) 947-0500

MARKED-UP COPY OF PARAGRAPH 2 ON PAGE 5

Similarly, the shock absorbing pad, that is associated with the sleeve, is also formed of a relatively flexible impact resistant material (e.g., expandable foam or elastomer). The material of choice for this pad (e.g., neoprene rubber) is relatively flexible at an effective impact absorbing thickness, which is typically less than about 0.25 inches and at least about 0.125 inches in thickness.

B1 It is understood that the thickness of the shock absorbing pad is limited by practical considerations relative to flexure of the guard and effectiveness in protection. In the preferred embodiments of this invention, the composite structure resulting from the sleeve and shock absorbing pad achieve the requisite protection without adding substantial weight to the device, or causing movement limiting restriction on the athlete's forearm. In another of the preferred embodiments of this invention, the impact resistant pad is either permanently affixed to the sleeve, or alternatively, releasably attached to the sleeve with a [Velcro-like fastener.] Velcro®-like hook and loop.
